




COMANSA

1600 Series

16LC185

17,640 lb



1600 Series

DTA Doble Carro SR/DR Automático. / Double Trolley Automatic SR/DR. / Double Chariot SM/DM Automatique. / Doppel Katze mit automatischer Umschierung. / Carrello doppio SR/DR automatico. / Автоматическое переключение на двоенную каретку.

STM Simple Carro SR/DR Manual. / Simple Trolley Manual SR/DR. / Simple Chariot SM/DM Manuel. / Einfach Katze mit manueller Umschierung. / Carrello singolo SR/DR manuale. / Механическое (ручное) переключение на одинарную каретку.


CE EN 14439


MECANISMOS

Mechanisms / Mécanismes / Antriebe / Meccanismi / Механизмы

	CFU-4.0
	5.4 hp
0 ⇔ 262 ft/min	

	GFU-7.5
	2x 10 hp
0 ⇔ 0.7 rpm	

	TRA-7.5
	2x 55 ft·lb
	78 ft/min
	3XR52

	TRA-7.5
	2x 55 ft·lb
	78 ft/min
	5XR72

Elevación / Hoist / Levage / Hub / Sollevamento / Тип механизма (подъем)	Carro / Trolley / Chariot / Laufkatze / Carrelo / Грузовая тележка	Giro / Slewing / Rotation / Drehbewegung / Rotazione / Поворот	Traslación / Travel / Translation / Verfahrbewegung / Traslazione / Ход	Tensión de alimentación / Operating voltage / Tension de service / Betriebsspannung / Tensione di alimentazione / Напряжение источника питания	Potencia requerida / Required power / Puissance requise / Benötigte Leistung / Potenza richiesta / требуемая мощность
EFU4-24-20	CFU-4.0	(2x) GFU-7.5	(2x) TRA-7.5	480 V	39 kVA
EFU4-37-20				3 ph 60 Hz	52 kVA


Opcional / Optional / En option / Kaufoption / Opzionale / Опционально
*

ALTURAS BAJO GANCHO

Heights under hook / Hauteurs sous crochet / Hakenhöhen / Altezza sotto gancio / Высота под крюком

∅ 6.6 ft

1600 Series



n°	Ref.	∅	h
1	S23	6.6	18.0
2	TS24	6.6	18.0
3	S24	6.6	18.0
4	TS25	6.6	18.0
5	S25	6.6	18.0

1x S23 = 1x S23M
1x S25 = 1x S25M

GRÚA ARRIOSTRADA

Braced crane / Grue à entretoisement / Abgespannter Kran / Gru ancorata / Нарастиваемый кран

∅ 6.6 ft

DTA (H) C/25	3XA52	5XA72
A max	131.6	168.6
A min	59.4	96.5
B max	-	72.2
B min	-	54.1
C max	116.8	116.8
H max	248.4	320.5

DTA (H) C/25	ES32	ES52	ES72
A max	108.6	126.6	162.7
A min	54.5	54.5	90.6
B max	-	72.2	72.2
B min	-	54.1	54.1
C max	116.8	116.8	116.8
H max	225.4	297.6	315.6

STM (H) C/25	3XA52	5XA72
A max	131.6	168.6
A min	59.4	96.5
B max	-	72.2
B min	-	54.1
C max	113.5	113.5
H max	245.1	317.3


STM (H) C/25	ES32	ES52	ES72
A max	108.6	126.6	162.7
A min	54.5	54.5	90.6
B max	-	72.2	72.2
B min	-	54.1	54.1
C max	113.5	113.5	113.5
H max	222.1	294.3	312.3

Otras zonas de viento, alturas superiores, arriostramientos o trepado interno consultar / Other wind zones, additional hook heights, tie frames or internal climbing on request / Autres zones de vent, des hauteurs supplémentaires, entretoisements ou grues avec cage de télescopage intérieure, sur demande / Andere Windzonen, weitere Hakenhöhen, Abspannungen zum Gebäude oder Klettern im Gebäude auf Anfrage / Per zone con velocità del vento particolari, altezze superiori, ancoraggi o rampante in cavedio, consultare il fabbricante / При других ветренных зонах, при большой высоте, привязках к зданию или наращивании крана внутри здания проконсультируйтесь с нами

GRÚA TREPADORA

Internal climbing crane / Grue avec cage de télescopage intérieure / Kran mit klettern im Gebäude / Gru in rampante in cavedio / Кран с самоподъемом

Ø 5.2 ft



DTA (H) C/25	Hs < 1,310 ft	
	A max (ft)	A min (ft)
153.5 ft 8x S15 + CLS15-08	64.3	36.1
135.5 ft 7x S15 + CLS15-08	55.1	29.5
117.5 ft 6x S15 + CLS15-08	46.3	23.0

STM (H) C/25	Hs < 1,310 ft	
	A max (ft)	A min (ft)
150.3 ft 8x S15 + CLS15-08	64.3	36.1
132.2 ft 7x S15 + CLS15-08	55.1	29.5
114.2 ft 6x S15 + CLS15-08	46.3	23.0

Ref.	Ø	h
S15	5.2	18.0
CLS15-08	5.2	10.2
1x S15 = 1x S15M		

Otras zonas de viento, alturas superiores, arriostamientos o trepado interno consultar / Other wind zones , additional hook heights, tie frames or internal climbing on request / Autres zones de vent, des hauteurs supplémentaires, entretoisements ou grues avec cage de télescopage intérieure, sur demande / Andere Windzonen, weitere Hakenhöhen, Abspannungen zum Gebäude oder Klettern im Gebäude auf Anfrage / Per zone con velocità del vento particolari, altezze superiori, ancoraggi o rampante in cavedio, consultare il fabbricante / При других ветренных зонах, при большой высоте, привязках к зданию или наращивании крана внутри здания проконсультируйтесь с нами

1600 Series